


PROFILES and GUIDES

TECHNICAL DATA SHEET

L40 blue ES580 CODE **TYPE**

DESCRIPTION

PVC inclined lateral profile.



TECHNICAL SPECIFICATIONS

	01146 (1	.,	olyvin		Material
Sh.A	60 ±5				Hardness
Blue					Colour
ved	Groo				Base
in.	0.91	mm	23		B Upper base
in.		mm			b Bottom base
in.	1.57	mm	40		H Height
oz/in	0.360	gr/m	405		Weight
					Minimum pitch
in.		mm			longitudinal
in.	2.2	mm	55		■ transversal
				ers ⁽¹⁾	Minimum pulley diamet
in		mm		ide	longitudinal-driving s
in		mm		g side	longitudinal-conveyi
in	3.2	mm	80	g side	transversal-conveying
	,C	ons of 20°	nt condition	ed to environme	(1) Minimum pulley diameters refer
٥F	14	°C	-10	min.	Temperature
۰F	140	°C	60	max	resistance (2)
				e its life	(2) Use with limit values may reduce
ft	7.9	m	2.4		Roll/bar sizes

COMPLIANCES

REACH EC 1907/2006 Regulation and Amendments FDA (Food and Drug Administration)

METHOD OF APPLICATION

NOTES

Issue 22-01-2020 Last Update: 22-01-2020

DISCLAIMER

The information contained in this document describes the features of the CHIORINO product as tested in a laboratory environment at a temperature of +23 degrees °C at 50% relative humidity. It does not necessarily reflect the conditions of industrial use and it does not guarantee the product to be suitable for certain applications. The client remains liable for the proper selection and correct use of the CHIORINO product. CHIORINO cannot be held responsible should damages arise from the use of its products. Necessary alterations to this data can be made without prior notice.